

FELT MELANGE



612



642



640



650



641



652



858



651



582



846



859



847



855



848



619



849



635



620



623



610

FELT MELANGE

EN

Composition:	70% Wool, 25% Polyamide, 3% Acrylic, 2% Polyester
Maintenance:	Vacuum regularly or © professional Dry-clean
Abrasion Resistance:	90.000 Martindale cycles
Flammability:	EN 1021 part 1&2 BS 5852-1: 1979

DE

Zusammensetzung:	70% Wolle, 25% Polyamid, 3% Akryl, 2% Polyester
Reinigung:	Regelmässig staubsaugen. © Professionelle Trockenreinigung
Scheuerfestigkeit:	90.000 Martindale
Feuerschutz:	EN 1021 part 1&2 BS 5852-1: 1979

FR

Composition:	70% Laine, 25% Polyamid, 3% Acryl, 2% Polyester
Nettoyage:	Aspirer régulièrement. © Nettoyage á sec professionnel
Résistance á l'abrasion:	90.000 cycles Martindale
Normes au feu:	EN 1021 source d'ignition 1&2 BS 5852-1: 1979

DK

Materiale:	70% Uld, 25% Polyamide, 3% Akryl, 2% Polyester
Rengøring:	Støvsug regelmæssigt eller © professionel rens
Slidstyrke:	90.000 Martindale
Flammesikring:	EN 1021 part 1&2 BS 5852-1: 1979